RBX270/270F

SERVICE MANUAL



WARNING: CHEMICAL CONTENT NOTICE!

The solder used in the production of this product contains LEAD. In addition, other electrical/electronic and/or plastic (Where applicable) components may also contain traces of chemicals found by the California Health and Welfare Agency (and possibly other entities) to cause cancer and/or birth defects or other reproductive harm.

DO NOT PLACE SOLDER, ELECTRICAL/ELECTRONIC OR PLASTIC COMPONENTS IN YOUR MOUTH FOR ANY REASON WHAT SO EVER!

Avoid prolonged, unprotected contact between solder and your skin! When soldering, do not inhale solder fumes or expose eyes to solder/flux vapor!

If you come in contact with solder or components located inside the enclosure of this product, wash your hands before handling food.

CONTENTS

OVERALL ASSEMBLY	. 2
CIRCUIT DIAGRAM	
WIRING	. 4
SPECIFICATIONS	

This document is printed on chlorine free (ECF) paper with soy ink.



OVERALL ASSEMBLY

(E17) Bridge Assembly: YP-02 (Chrome) (A01a) **B08** A seal is attached **B05 B06** on the rear of the neck. (B03) ((RBX270)) B07 (RBX270F) (B02) **B04**) B02 **E01 E04 B05** (B07) E02 E04 B02 **E10** (E05) **B07 (E07) B01 B08 B06**) **B02 B08** (A01) **E20** (F11) Jack (F11a) F11c) **E24**) **E23** (F11b **E25** 0 **D02 E11**) 0 (E12) 0 E08 E09 **E29 E31** G01)G04 **G03** E27 F01a MASTER VOLUME: 15A 250K Ω 0 (F01) **G08 E27** (F01c) G06 G09 BALANCER: 1Z 250KΩ X 2 E27 F01b F01d **E17**) MASTER TONE: 05A 250K Ω **E18** (F11) **E25**) **E23**


E24)


	PART NO.	DESCRIPTION	REMARKS	QTY	Υ
		OVERALL ASSEMBLY	RBX270/RBX270F		
401	AAX25830	Neck Assembly	RBX270		
401	AAX28750	Neck Assembly	RBX270F		
.01a		Seal	RBX270 (QC6161	ω	
.01a		Seal	RBX270F (QC6246	U)	
202		Dody			
002		Body			
=01	00207000	Tuning Machine Assembly	RM1243 (Chrome)	2	.
E01			RM1243 (Chrome)	2	
02	QC236900		· · · · · · · · · · · · · · · · · · ·	2	
04	EA620040		2.4X10 (Chrome)	4	٠
05	AA820810	String Guide	(Chrome)		
07	EA620070	Round Head Wood Screw	2.7X20 (Chrome)	2	:
80	CB821460	Rod Cover	(Black)		
09	03706220		2.1X10 (Black)		
10	CB821090				
			Urea 40mm (Ivory)		
11	AA819690		(Chrome)		
12	EN240060	Oval Head Tapping Screw	4.0X45 (Nickel)	4	.
17	VD862300	Bridge Assembly	YP-02 (Chrome) 1set		
18		Oval Head Tapping Screw	3.0X25 (Nickel)	5	
20		Strings	1set (QC3510		
					.
23	BB801510		ST-type (Chrome)	2	
24	EN230140		3.0X25 (Nickel)	2	
25	VB793700	Spacer	Felt (Black)	2	1
27	QA211100		(Black)	3	
29	CB809560		(Black)		
31	EB620020	Oval Head Wood Screw	2.7X13 (Black)	4	
.01	LD020020	Oval Head Wood Sciew	2.17(10 (DIGUR)	4	
01		Electrical Unit	(VD8632	0)	
-			15A 250K ohm MASTER VOLUME	~,	
01a		Variable Resistor			
01b		Variable Resistor	05A 250K ohm MASTER TONE		
01c	VB518700	Variable Resistor	1Z 250K ohm x2 BALANCER		
01d	UA114470	Mylar Capacitor	0.047uF 50 J		
11	QA209900	Jack			
11a		Hexagonal Nut			
11b		Flat Washer			
11c		Rubber Ring			
204	00005100	Dielana Assessible	FROUT		
301		Pickup Assembly	FRONT		
303	A7388800		2.6X35 (Black)	4	
304	CB817760	Pickup Cushion		2	: [
306		Pickup Assembly	REAR		
806	VJ388800		2.6X35 (Black)	4	
			2.0//00 (Diauk)	4	
909	CB815450	Pickup Cushion			
104	OC2E 4000	Acceptant	(C 1)		
101		Accessory Unit	(G-1) 1set		
	QA262600	Cord	D		
		Wrench	#1.5		
		Wrench	#5		
	VD862300	Bridge Assembly	YP-02 (Chrome)	1	
301	AA862300		(Chrome)		
302	AA809350		(Chrome)	4	
	EA130406	Pan Head Screw			
303			3.0X40 (Chrome) 1,2 string	2	
04	EA130356		3.0X35 (Chrome) 3,4 string	2	
05	QA014700		L=35 1,2 string	2	
306	QA014800	Bridge Spring	L=25 3,4 string	2	1
307	EX801620	Set Screw	3.0X12 (Chrome) 1,4 string	2	
808	EX801630		3.0X14 (Chrome) 2,3 string	2	
			2,0 000119	-	

*: New Parts RANK: Japan only

■ CIRCUIT DIAGRAM

WIRING





SPECIFICATIONS

RBX270

• STANDARD SPECIFICA	TIONS
Scale Length	863.6mm
Body-Neck Construction	Bolt On
Length	1118mm
Width	327mm
Net Weight	
● COLŎR	9
Body	
BL	Black
MGR	Mist Green
MRB	Mist Raspberry
MPP	Mist purple
YNS-O	Yellow Natural Satin
RM	Red Metallic
Neck	
NS	Natural Satin
● BODY	
Material	Alder
Body Depth	
● FĬNGĒRBOARD	
Material	Rose
Fingerboard Width	0-F 40.0 mm, 12-F 56.4 mm
No. of Frets	
● NECK	
Material	Maple
Neck Thickness	1-F 21.0 mm, 12-F 24.4 mm
• PARTS	
Hardware	Chrome Plated
Nut	Urea
Bridge	Vintage Type: YP-02
Strings	Korea
● CONTROLS	
Volume	15A 250KΩ x 1
Tone	05A 250KΩ x 1
Balance	1Z 250KΩ x 1
• PICKUPS	
Front	Single Coil Split Type
Rear	Single Coil
Magnet	
Front/Rear	Ferrite

RBX270F

■ STANDARD SPECIFICA	
Scale Length	863.6mm
Body-Neck Construction	Bolt On
Length	1118mm
Width	327mm
Net Weight	3.3 kg
● COLŎR	
Body	
BL	Black
MGR	Mist Green
Neck	
NS	Natural Satin
● BODY	
Material	Alder
Body Depth	41mm
● FINGERBOARD	
Material	Rose
Fingerboard Width	0-F 40.0 mm, 12-F 56.4 mm
● NECK	
Material	Maple
Neck Thickness	1-F 21.0 mm, 12-F 24.4 mm
● PARTS	
Hardware	Chrome Plated
Nut	Urea
Bridge	Vintage Type: YP-02
Strings	Korea
● CONTROLS	
Volume	
Гопе	05A 250KΩ x 1
Balance	1Z 250KΩ x 1
● PICKUPS	
Front	Single Coil Split Type
Rear	
Magnet	-
Front/Rear	Ferrite